

PM Cladding Power Stripper

Features:

Low insertion loss
High Efficiency
stability and reliability

Application:

Wave Fiber Laser
High-Power Laser Equipment
Experimental tests and other areas

Description	Parameter	Unit	Note
Type	PMCPS		
Pump Wavelength	916	nm	
Signal Wavelength	1064	nm	
Input Fiber	PM10/125 DCF 0.07/0.46NA	μm	
Signal Fiber	-	μm	
Output Fiber	PM10/125 DCF 0.07/0.46NA	μm	
Signal Insertion Loss	0.2	dB	
Stripping Efficiency	20	dB	
Signal Output Beam M ²	1.2	-	
Pump Power Handling	10	W	
Signal Power Handling	-	W	
ER	20	dB	
Operating Temperature	-5-+70	°C	
Storage Temperature	-20-+70	°C	
Fiber Length	1.0	m	
Dimensions	70x12x8	mm	Handling power is different with PKG

Mechanical Dimension



Ordering Information

GPMCPS-1x1-1-2-3-4-5-6-7

1	Pump Wavelength	916 - 916nm Other - Specify
2	Signal Wavelength	1064 - 1064nm Other - Specify
3	Input Fiber Type	PM10/125 DCF 0.07/0.46NA Other - Specify
4	Output Fiber Type	PM10/125 DCF 0.07/0.46NA Other - Specify
5	Power Handling	10W - 10 W power
6	Package Type	X-70x12x8mm Other - Specify
7	Fiber Length	1 m- 1meter Other - Specify