

Fiber Connector(CONN)

Features

Low insertion loss
High extinction ratio
High stability & Reliability

Applications

Fiber Amplifier
Fiber sensor
Fiber Laser Marking
Laboratory R&D

Parameter		Fiber Connector	Unit
		Single Mode	
Operating wavelength		980/1060	nm
Fiber type		HI1060 or HI1060flex	-
Grade		A	-
Insertion loss		≤ 0.4	dB
Return loss	UPC	≥ 50 dB	dB
	APC	≥ 60 dB	dB
Repeatability		/	dB
Changeability			dB
Durability		≥ 1000	-
Operating temperature		-40 ~ + 85	°C

*The fiber length & the fiber type are following the customer request for jumpers.

Ordering Information	
specification	GCCONN
Output Connector	FC/UPC, FC/APC, SC/UPC, SC/APC etc.
Input Connector	FC/UPC, FC/APC, SC/UPC, SC/APC etc.
Fiber Length	005=0.5m, 010=1.0m, 015=1.5m, 100=10m etc.
Fiber Type	0=SMF-28e, 1=HI1060flex, 2=50/125, 3=62.5/125, 4=others
Pigtail Type	0=250μm, 1=900μm, 2=2mm, 3=3mm, 4=others
CONN	Fiber Connector